	LATIODETE 4007D	Latera Aduata		
TRADE NAME (as labeled):	LATICRETE 423/R	LATICRETE 4237R Latex Admix Fast setting Mortar additive LATICRETE PTY LTD 29 Telford Street Virginia. QLD. 4014 1800 331 012, 07 38651599 www.laticrete.com.au 131126 21 October 2021		
USE:	Fast setting Mortar additive			
MANUFACTURER'S NAME:	29 Telford Street			
For additional information: Web address: Poisons Information Number: Date prepared or revised:	www.laticrete.com.au 131126			
	2. HAZARDS IDENTIFICAT	TION		
_				
•				
Goods substance according to the	cording to the criteria of the NOHSC. All con ADG code. Not classified as a scheduled p e criteria of AS 1940.			
Goods substance according to the combustible liquid according to the	ADG code. Not classified as a scheduled p			
Goods substance according to the combustible liquid according to the Risk Phrases: Xi Irritant.R36	ADG code. Not classified as a scheduled p	poison according to the SUSDP. Not cl		
Goods substance according to the combustible liquid according to the Risk Phrases: Xi Irritant.R36 Safety Phrases: S24 Avoid con	ADG code. Not classified as a scheduled pe criteria of AS 1940. tact with the skin. S25 Avoid contact with eye	poison according to the SUSDP. Not cl	assified as a flammab	
Goods substance according to the combustible liquid according to the Risk Phrases: Xi Irritant.R36 Safety Phrases: S24 Avoid con	ADG code. Not classified as a scheduled pe criteria of AS 1940.	poison according to the SUSDP. Not cl	assified as a flammab	
Goods substance according to the combustible liquid according to the Risk Phrases: Xi Irritant.R36 Safety Phrases: S24 Avoid con	ADG code. Not classified as a scheduled pe criteria of AS 1940. tact with the skin. S25 Avoid contact with eye	poison according to the SUSDP. Not cl	assified as a flammab	
Goods substance according to the combustible liquid according to the Risk Phrases: Xi Irritant.R36 Safety Phrases: S24 Avoid con	ADG code. Not classified as a scheduled pe criteria of AS 1940. tact with the skin. S25 Avoid contact with eye	poison according to the SUSDP. Not cl	assified as a flammab	
Goods substance according to the combustible liquid according to the Risk Phrases: Xi Irritant.R36 Safety Phrases: S24 Avoid con	ADG code. Not classified as a scheduled pe criteria of AS 1940. tact with the skin. S25 Avoid contact with eye	es. RMATION ON INGREDIENTS	assified as a flammab	
Goods substance according to the combustible liquid according to the Risk Phrases: Xi Irritant.R36 Safety Phrases: S24 Avoid con	ADG code. Not classified as a scheduled pe criteria of AS 1940. tact with the skin. S25 Avoid contact with eye	es. RMATION ON INGREDIENTSCAS NUMBERS	assified as a flammab	

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: No adverse effects are anticipated from inhalation

Contact with eyes: Eye contact may cause slight, temporary eye irritation.

Contact with Skin: Short exposure not likely to cause significant skin irritation. Skin absorption is unlikely due to physical properties.

Swallowed: Single dose oral toxicity is believed to be Moderate. No hazards anticipated from ingestion incidental to industrial exposure.

Page 1 of 4

LATICRETE 4237R Latex Admix

Material Safety Data Sheet

FIRST AID or EMERGENCY PROCEDURES

Eye Contact: Wash the eyes with large amounts of water for 15 minutes, occasionally lifting the lower and upper lids. If symptoms persist get medical attention promptly.

Skin Contact: Remove contaminated clothing. Promptly wash contaminated skin with water for 3-5 minutes and thensoap or mild detergent and water. If symptoms persist seek medical attention promptly.

Inhaled: Safely move the exposed person to fresh air at once and allow to rest. Provide artificial respiration if breathing stops. Seek medical attention unless recovery is immediate.

Swallowed: If the person is conscious, give large amounts of water. Do not induce vomiting. Get medical attention immediately.

First aid facilities

Provide normal industrial first aid facilities, eye wash station and safety showers as appropriate.

Notes to Physician

Possible aggravated pre-existing conditions – none reported.

Suggested treatment for acute symptoms, known antidotes – Provide care and treatment based on the patients reaction to the exposure. For further information contact the; Poisons Information Centre 131126 in all states (New Zealand Dial 0800764766)

	5. FIRE AND EXPL	OSION	
Flash Point, °C (give method): Auto ignition temperature, °C:	Not flammable or combustible N/A		
Flammable limits in air, volume %:	N/A Lower (LEL)	Upper (UEL)	
Fire extinguishing materials: x water spray foam	N/A carbon dioxide dry chemical	other:	
Hazchem Code: Not allocated			
Special fire fighting procedures: N/A	A	add to combustible load in the event of a fire. stible, however the dried resin is combustible similar to wood.	Burning dry
	6. ACCIDENTAL RE	ELEASE MEASURES	

Emergency Procedures – Spills and Leaks - Include employee protection measures: Flush area with water immediately. Avoid unnecessary exposure and contact. Wear safety glasses and impervious gloves.

Prevent from entering drains and waterways.

Preparing wastes for disposal (container types, neutralization etc): Soak up with absorbent materials. Store in pails or drums. Bury in approved landfill or burn solid wastes in an adequate incinerator. If enters sanitary sewers, flush with large amounts of water.

Notify relevant authorities if it enters drains and waterways.

Page 2 of 4

LATICRETE 4237R Latex Admix

Material Safety Data Sheet

Disposal: Recycle wherever possible or consult manufacturer for recycling options. Dispose of in an authorized landfill according to federal, state and local regulations.					
	- 7. HANDLING AND STORAGE				
Handle with suitable personal protective equipme	nts, clothing.				
Avoid skin or eye contact.					
Suitable Containers Check all containers are clearly labeled and free t	rom leaks.				
manufacturers storing and handling recommend					

No exposure standards for this product have been set:					
Substance	TWA	STEL			
SBR copolymer	N/A	N/A			
Calcium Chloride	N/A	N/A			
N/A = Not applicable or Not available Ventilation and engineering controls: If used e or airborne particle levels are excessive or unco	externally natural ventilation is generally adequate. mfortable.	Ventilate confined small spaces where mists			
Respiratory protection (type): No respiratory proganic vapour filters to AS1715 & AS1716 in an	otection is should be required if good ventilation is eas with high vapour concentrations.	maintained. Use respirators fitted with			
Eye protection (type): Use a chemical goggle of	r safety glasses with side shields or safety glass to	AS1337.			
Gloves (specify material): Use impervious gloves, vinyl or rubber to AS2161.2					
Other clothing and equipment: Wear clean, lon	g-sleeved, body covering clothing.				
Work practices, hygienic practices: Familiarize contaminated clothing and clearing of contaminated	the employees with the handling procedures in thated areas.	is section; also encourage prompt removal of			
	9. PHYSICAL PROPERTIES				
Vapor density (air=1): N/A	Melting point or range, °C:	N/A			
Specific gravity: 1.00	Boiling point or range, °C:	100			

Evaporation rate (butyl acetate = 1): N/A

Page 3 of 4

Solubility in water: Emulsion

Vapor pressure, mmHg at 20 ° C: 0mm

Appearance and odour: White liquid, slight odour

LATICRETE 4237R Latex Admix

Material Safety Data Sheet

	10. REACTIVITY DATA					
Stability:	X Stable	Unstable				
Conditions to avoid: May coagulate if frozen at 0	0 ℃					
Incompatibility (materials to avoid): N/A						
Hazardous decomposition products (including combustion products): (from burning, heating or reaction with other material): None						
Hazardous polymerization:	May occur	XWill not occur				
	11 . TOXICOLOGICAL INFORM	MATION				
No relevant product data found	. 12 ECOLOGICAL CONSIDED	ATIONS				
May have an adverse effect on aquatic organisms if large amounts are released to waterways.						
, ,	•	ONS				
Dispose of all wastes in accordance with federal, state and local regulations for non-hazardous chemical wastes						
	- 14. TRANSPORT CONSIDERA	ATIONS				
•						
Requirements under the ADG code, IMDG code, or the IATA DG code do not apply to this product						
	- 15. REGULATORY INFORMA	TION				
Label in accordance with the National Code of PraSUSDP or the ADG Code is not required.	actice for the Labeling of Workplac	e Substance (NOHSC: 2012 (1994)): Labeling under the				
	16. OTHER INFORMATION					

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate. Persons dealing with the products referred to in this MSDS do so at their own risk since their actions are beyond our control. Laticrete Pty Ltd accepts no liability whatsoever for damage or injury arising from the use of the information contained in this document. This document should be made available to all operators who may come into contact with this product.