CONCRETE TROWELLING MACHINES

"G SERIES" - COMBINATION OR DUAL BLADE MODELS

FEATURES

- * Sealed Base robust sealed base and tilting mechanism minimises maintenance costs.
- * Balance low centre of gravity ensures stability and balance for better finishing, reduced operator fatigue and backache.
- * Adjustable handles wide handles with adjustable height ensure operator comfort and ease of control.
- * Safety runaway prevention switch , plus vee belt, clutch guard and blade guard.
- * Heavy duty durable finish for quick cleanup and lasting good looks.
- * Finger tip blade tilting mechanism control.
- * Ease of control with blade tilt, throttle and cutout switch mounted on handlebar stem.
- * Site Handling optional crane hook is standard.
- Jockey wheel standard for ease of manoeuvring.
- * Sprayer holder for applying water & carrying extra weight standard.



BLADE STYLES



MODEL CHOICE

34" & 40" machines powered by Honda GX160, 5,5HP motor

C+ C+O Madrimos powered by Heriad CATTON, COTTI Model					
Description	HP	Ring Diameter	Weight	Blade Choice	Model Code
34" Fixed Ring Guarded	5.5	900mm	70Kg	S34-18 Combination	G34C
				D34-3 Finishing	G34F
40" Fixed Ring Guarded	5.5	1060mm	75Kg	S40-18 Combination	G40C
				D40-2 Finishing	G40F